



# RUBBERIZED UNDERCOATINGS

## TECHNICAL DATA SHEET

### Description

**39523 RUBBERIZED UNDERCOATING** and **40523 LOW VOC RUBBERIZED UNDERCOATING** are paintable, fast-drying, asphalt free coatings for rust proofing, sound deadening, chip resistance and corrosion protection. **40523** is less than 40% VOC.

### Features

- Asphalt free
- Paintable
- Sound-deadening properties
- Fast-drying
- Chip resistant
- Corrosion protection

### Typical Properties

Container	24 oz. aerosol
Color	Black
VOC <b>39523</b>	4.84 #/gl (580.8 g/l)
VOC <b>40523</b>	2.79 #/gl (334.2 g/l)
Paintable	Yes

### Handling and Application

**PREPARATION:** Clean surface with **3837( ) SEM SOLVE**. Remove any loose paint, rust, oil and grease. Blow off and clean again with **3837( )**.



**APPLICATION:**

Distance:	6-8"
Coats:	2-3 medium wet
Flash time:	3-5 minutes



**NOTE:** If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.

**NOTE:** After each use, turn can upside down and spray several seconds to clear spray tip.

**STORAGE:** **39523 RUBBERIZED UNDERCOATING** and **40523 LOW VOC RUBBERIZED UNDERCOATING** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **39523** and **40523** is 3 years when stored under normal conditions.



### TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

**DISCLAIMER:** The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.