

1 PORT BLOWER

ULTRA-SMALL DESIGN

FAA/PMA (Pending)

Lone Star Aviation's new 1 Port Blower is the smallest (1"x 2"x 2"), most efficient (Brushless DC Motor), and most versatile avionics cooling fan in our industry today. This NEW Blower's universal mounting bracket makes it easy to set-up and install on a variety of aircraft. Install immediately on experimental, sport, and soon on general aviation, business, and commercial class aircraft.

- Ultra-Small size 1"x 2"x 2"
- Light Weight 52 grams / 0.115 lbs
- Brushless Motor - (Ball Bearing)
- Models: 12V or 24V
- Max Air Flow 6.7 CFM
- Speed 4500 rpm
- Max. Static Pressure in H₂O 0.64
- Universal Mounting Bracket
- Voltage Range (12vdc): 10.2 - 15.8V
- Current (12vdc): 0.320mA
- Voltage Range (24vdc): 18.2 - 27.5V
- Current (24vdc): 0.300mA
- Operating Temp: -55C to +70C
- Easy Installation
- FAA PMA (Pending)



→ Customers that purchased the 1P Fan purchased the following:

- Separate Lengths of 5/8" Tubing LS03-04000
- A 50 ft. Roll of 5/8" Tubing LS03-04000-50

→ Blowers with (3 or 6) ports:

- Cyclone 21 - 3 Port (12 or 24 vdc) CRB-6457 / CRB-122253
- Cyclone 600 - 6 Port (12 or 24 vdc) LS03-03034 / LS03-03035



P/N FOR 1 PORT BLOWER & ACCESSORIES		
Item	Product Description	Part Number
1	1 Port Fan 12V Model	LS03-02040
2	1 Port Fan 24V Model	LS03-02041
3	Tubing 5/8" - 50 ft. Roll	LS03-04000
1 YEAR LIMITED WARRANTY		



CALL NOW TO ORDER

604 S. Wisteria St. • Mansfield, TX 76063
 Ph (682) 518-8882 • Fax (682) 518-8831
www.lonestaraviation.com
sales@lonestaraviation.com



WE SHIP
WORLDWIDE!

