

Safety Data Sheet
Light

SECTION I - IDENTIFICATION

PRODUCT NAME: Light
PRODUCT CODE: 1062350
PRODUCT USE: Penetrating lube
COMPANY NAME: Aviation Laboratories
COMPANY ADDRESS: 5401 Mitchelldale #B-6, Houston, TX 77092
COMPANY PHONE: 713-896-8188
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Dissolved Gas

Eye Irritant: Category 2b

Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Contains gas under pressure; May explode if heated. Causes eye irritation. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



SYMBOL:

HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Isoparaffinic Hydrocarbon	64742-47-8	40-70%
Mineral Seal Oil	64741-44-2	15-40%
Carbon Dioxide	124-38-9	1-5%
Dipropylene glycol monomethyl ether	34590-94-8	1-5%
Naphthenic Petroleum Distillate	64742-53-6	1-5%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration. Seek immediate medical attention.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Oral: abdominal irritation, nausea, vomiting, diarrhea, aspiration risk

CHRONIC HEALTH HAZARDS: None known

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam, or Carbon Dioxide (CO₂).

Safety Data Sheet

Light

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Remove all sources of ignition, ventilate, avoid breathing vapors and remove all inert absorbent.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, some plastics.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Isoparaffinic Hydrocarbon	5 mg/m ³	5 mg/m ³
Mineral Seal Oil	200 mg/m ³	200 mg/m ³
Carbon Dioxide	5000 ppm	5000 ppm
Dipropylene glycol monomethyl ether	100 ppm	100 ppm
Naphthenic Petroleum Distillate	5 ppm (as oil mist)	5 ppm (as oil mist)

ENGINEERING CONTROLS / VENTILATION: General ventilation adequate.

RESPIRATORY PROTECTION: Not required with adequate ventilation

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Amber Spray

ODOR: Bland odor

ODOR THRESHOLD: N/D

BOILING POINT: N/D

FREEZING POINT: N/D

FLAMMABILITY: Not considered a flammable aerosol or an extremely flammable aerosol by OSHA (29CFR 1910.1200)

FLASH POINT: > 200°F (93°C)

AUTOIGNITION TEMPERATURE: N/D

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

VAPOR PRESSURE (mm Hg): 30 @ 77°C

VAPOR DENSITY (AIR=1): >2

EVAPORATION RATE: < 1

SPECIFIC GRAVITY (H₂O=1): 0.825

pH: N/A

SOLIDS (%): N/D

SOLUBILITY IN WATER: Non-soluble

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

VOLATILITY INCLUDING WATER (%): <10%

VOLATILE ORGANIC COMPOUNDS (VOC): 3%

Safety Data Sheet
Light

DIELECTRIC STRENGTH (Volts): N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: If exposed to strong oxidizers, presents explosion hazard.
CHEMICAL STABILITY: Stable
CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, some plastics.
HAZARDOUS DECOMPOSITION OR BY-PRODUCT: None Known
POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Isoparaffinic Hydrocarbon** (64742-47-8) Eye Damage/Irritation: 2B; Aspiration Hazard: Category 1 **Dipropylene glycol monomethyl ether** (34590-94-8) LD₅₀ (Oral, Rat) >5000 mg/kg; LD₅₀ (Dermal, Rabbit) 9510 mg/kg **Carbon Dioxide** (124-38-9) LC₅₀ (Inhalation, Rat, 30 min) 470,000 ppm

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation, redness, tearing.

INGESTION: May cause gastrointestinal irritation, nausea, diarrhea, vomiting, aspiration hazard.

INHALATION: Causes dizziness, excessive or prolonged exposure may cause unconsciousness.

SKIN: May cause irritation, localized defatting, dermatitis, with prolonged or repeated contact.

MEDICAL CONDITION AGGRAVATED: Pre-existing conditions of the skin, liver, CNS, and kidneys

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Oral: abdominal irritation, nausea, vomiting, diarrhea, aspiration risk

CHRONIC HEALTH HAZARDS: None known

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: **Isoparaffinic Hydrocarbon** (64742-47-8) Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility. May adsorb to sediments and possibly cause toxic effects to organisms.

BIODEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATION: This product is not expected to bioaccumulate.

SOIL MOBILITY: This product is mobile in soil.

OTHER ECOLOGICAL HAZARDS: None Known

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN 1950

SHIPPING BY WATER:

Safety Data Sheet
Light

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: UN 1950

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA 311/312 HAZARD CATEGORIES: Combustible Liquid, Reproductive hazard

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: This product contains no known chemicals regulated by California's proposition 65.

INTERNATIONAL REGULATIONS: All components are listed or exempted.

NFPA HEALTH:	1	HMIS HEALTH:	1
NFPA FLAMMABILITY:	1	HMIS FLAMMABILITY:	1
NFPA REACTIVITY:	0	HMIS REACTIVITY:	0
NFPA OTHER:	None	HMIS PROTECTION:	A

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: Jonathon Jarvis

DATE PREPARED: 12/30/2013

REVISION DATE: 04/07/2015

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.