

> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

1.1 APPLICABLE PART #: PC22051GL, PC22051QT, PC22055GL, PC22055GL, PC2205S, PC2205S2.

1.2 IDENTITY: NU-POL

1.3 INTENDED USE: CLEANER / POLISH

1.4 SUPPLIER: Universal Photonics, Inc. FOR INFORMATION CALL

85 Jetson Lane CUSTOMER SERVICE: (516) 935-4000
Central Islip, NY 11722 DATE PREPARED: February 13, 2019

1.5 EMERGENCY CONTACT: Verisk 3E™ - ACCT # 3665 Access Code: 333748

EMERGENCY TELEPHONE NUMBER: Domestic: 1-866-519-4752 International: +1-760-602-8700

SECTION 2: HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF SUBSTANCE: RESPIRATORY STOT RE1: H372; MUTAGENIC 1B: H340; CARCINOGEN 1A: H350;

RESPIRATORY STOT SE3: H335; ASPIRATION TOXICITY 1: H304;

SKIN IRRITATION 2: H315; EYE IRRITATION 2: H319; AQUATIC CHRONIC 3: H412

2.2 GHS LABEL ELEMENTS:





HAZARD PICTOGRAMS:

HAZARD SYMBOLS: GHS08 / GHS07 / GHS09

SIGNAL WORD: DANGER.

HAZARD STATEMENTS: H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.H335 May cause respiratory irritation.H340: May cause genetic defects.

H350: May cause cancer.

H372: Causes damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

PREVENTION PRECAUTIONARY

STATEMENTS:

P261: Avoid breathing dust/fumes/mist/vapors/spray.

P262: Do not get in eyes, on skin, or on clothing. P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection.

Wear protective gloves. Wear eye protection to include splash goggles.

Wear protective clothing. Use with ventilation. Wash hands after handling.



> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

RESPONSE PRECAUTIONARY: STATEMENTS:

P302 + P352: IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301 + P331 + P315: IF SWALLOWED: DO NOT induce vomiting. Get immediate medical advice/attention.

In the event of skin, eye, respiratory contact or ingestion, seek medical attention immediately.

STORAGE PRECAUTIONARY STATEMENTS:

P404: Store in a closed container.

DISPOSAL PRECAUTIONARY STATEMENT:

P501: Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 HAZARDS NOT OTHERWISE

CLASSIFIED:

None known.

2.4 UNKNOWN ACUTE TOXICITY: None known.

SECTION 3: COMPOSITION INFORMATION ON INGREDIENTS

3.1 **INGREDIENTS**:

COMPONENTS	IDENTIFIER	CLASSIFICATION	WEIGHT %
STODDARD SOLVENT	(CAS #) 8052-41-3 (EC #) 232-489-3	ASPIRATION TOXICITY 1: H304, FLAMMABLE LIQUID 2: H226, SKIN IRRITATION 2: H315, EYE IRRITATION 1: H319, INHALATION (CNS) STOT RE 1: H372 AQUATIC CHRONIC 2: H411	30 - 40
CRISTOBALITE (SiO ₂) QUARTZ**	(CAS #) 14464-46-1 (EC #) 238-455-4	RESPIRATORY STOT RE 1: H372; CARCINOGEN 1A: H350.	7
KAOLIN	(CAS #)1332-58-7 (EC #) 310-194-1	SKIN IRRITATION 2: H315; EYE IRRITATION 2: H319; STOT RE 1 (LUNG): H372	3
TRADE SECRET INFORMATION*	N/A	PROPRIETARY	>50

NOTE: *Non-regulated components are proprietary, confidential, and trade secret.

^{**} Note: Silica (SiO2) dust is minimized through the viscous embodiment of the product.



> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:	

SKIN: Remove soiled clothing and flush with soap and water.

EYES: Flush with water for 20 minutes and remove contact lenses if safe to do. Immediately seek

medical attention.

INHALATION: Administer fresh air or oxygen.

INGESTION: DO NOT induce vomiting. Immediately seek medical attention. If vomiting does occur,

keep head low so that vomit does not enter the lungs. Maintain an open airway.

4.2 MOST IMPORTANT SYMPTOMS / EFFECTS, ACUTE AND DELAYED:

SKIN CONTACT: Will cause dryness, irritation and defatting upon prolonged contact.

EYE CONTACT: Will cause serious eye irritation upon direct contact.

INHALATION: Breathing high concentrations of sprayed mists will irritate nose and throat.

INGESTION: Will cause serious gastric disturbances.

ENVIRONMENT: None known.

CHRONIC: None known.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY:

Immediately contact physician for further medical advice.

SECTION 5: FIREFIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

SUITABLE EXTINGUISHING MEDIA: Water spray, alcohol resistant foam, dry chemical, CO₂.

UNSUITABLE EXTINGUISHING MEDIA: None.

5.2 SPECIFIC HAZARDS ARISING FROM THE MIXTURE:

FIRE HAZARD: None.

EXPLOSION HAZARD: None.

REACTIVITY: None.

EXPOSURE HAZARDS: Oxides of carbon, oxides of nitrogen.

UNUSUAL FIRE/EXPLOSION HAZARD: None known.

5.3 SPECIAL PROTECTIVE EQUIPMENT: Wear full protective safety equipment as standard practice. In the event of fire, wear

self-contained breathing apparatus.



> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

NON-EMERGENCY PERSONNEL: Wear appropriate personal protective equipment (PPE). Avoid contact with skin and eyes.

Do not walk through spilled material. Provide ventilation with sufficient face velocity to maintain PEL below standard. Supplement with appropriate organic vapor & dust respirator

when ventilation is inadequate.

EMERGENCY RESPONDERS: Take note of any special instructions in Section 8.

6.2 ENVIRONMENTAL PRECAUTIONS: Do not introduce material directly into natural waterways such as rivers, lakes,

streams, etc. or drains and sewers.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN-UP:

SMALL SPILL: Stop leak if safe to do so. Use inert absorbent material and dispose in proper chemical

waste container or to approved waste treatment areas.

LARGE SPILL: Stop leak if safe to do so. Approach release from upwind. Prevent entry into sewers or

natural waterways. Contain and collect with inert absorbent material and place in container for disposal according to local regulations (See Section 13). Dispose via a

licensed waste disposal contractor.

6.4 REFERENCE TO OTHER SECTIONS: See Section 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING: Minimize exposure to vapors or dusts. Use recognized standard safety practices to include

adequate ventilation. Handle with care to avoid contact. Wash with soap & water after handling. Use recognized standard safety practices. Provide sufficient air exchange and

exhaust in work areas. Eyewash station should be in close proximity to work

7.2 CONDITIONS FOR SAFE STORAGE: When not in use, keep closure on container tightly closed. Store indoors. Keep away from

heat and freezing conditions.



> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

OCCUPATIONAL EXPOSURE LIMITS: FOR INGREDIENTS:

			WORKPLACE EXPOSURE LIMIT (WEL)				
COMPONENTS	COMPONENT IDENTIFIERS	Lī	rel	STE	L	SUPPLEMENTAL EXPOSURE LIMIT VALUES	BASIS
		PPM	MG/M3	PPM	MG/M3		
STODDARD	(CAS #) 8052-41-3					500 PPM TWA	OSHA
SOLVENT	(EC #) 232-489-3					100 PPM TWA	ACGIH
CRISTOBALITE	(CAS #) 14464-46-1					25 μg/m³ RESPIRABLE TWA	OSHA
(SiO ₂) QUARTZ	(EC #) 238-455-4					0.025 mg/m ³ RESPIRABLE TWA	ACGIH
	(0.4.0 (1).4.0.0 = 0.7					5 mg/m3 RESPIRABLE PEL	OSHA
KAOLIN	(CAS #)1332-58-7 (EC #)310-194-1					15 mg/m3 TOTAL DUST PEL	OSHA
						2 mg/m3 TWA TLV	ACGIH

8.2 EXPOSURE CONTROLS:

CONTROL PARAMETERS: General ventilation with adequate face velocity to control worker exposure to airborne

contaminants below PEL. Supplement with NIOSH approved organic vapor cartridge respirator. Insure that emergency eyewash stations are in the immediate vicinity of any

potential exposure.

ENGINEERING CONTROLS: If user operations generate dust, fumes, vapor or mist, use process enclosures, local

exhaust or other engineering controls to keep worker exposure below any

recommended or statutory limits.

PERSONAL PROTECTIVE CONTROLS:

HYGIENE MEASURES: Wash hands, forearms and face thoroughly after handling product. Remove

contaminated clothing and wash before reusing. Ensure that eyewash stations and

safety showers are close to the workstation location.

SKIN PROTECTION: Chemical-resistant, impervious gloves are recommended if exposure is prolonged—

neoprene type. Inspect gloves on a routine basis for retention of properties. Personal protective clothing for the body should be selected based upon the task being performed.

EYES: Avoid eye contact. Protective safety eyewear goggles are recommended to avoid

exposure to liquid splashes, mists, and dusts or when working on overhead structures if direct contact is evident. Face shield is also recommended if splashing is evident.

RESPIRATORY: Should vapors exceed permissible exposure limit (PEL), wear NIOSH-approved dust and

organic vapor respirator.



> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

8.3 PERSONAL PROTECTIVE EQUIPMENT (PPE):









SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE Liquid, viscous

COLOR White.

ODOR: Solvent.

ODOR THRESHOLD Not determined

PH 10.8 - 11.5 @ 25°C.

SOLUBILITY: Dispersible

FLASH POINT: 62 °C / 142°F

LOWER FLAMMABLE LIMIT None

UPPER FLAMMABLE LIMIT None

AUTOIGNITION TEMPERATURE Not applicable

DECOMPOSITION TEMPERATURE Not applicable

FLAMMABILITY: Not applicable

SPECIFIC GRAVITY: 0.95 at 25°C

BOILING POINT (°F): 212 °F

VAPOR PRESSURE: 18 at 20°C

VAPOR DENSITY: Greater than 1 (Air = 1)

MELTING POINT (°F): Not applicable

FREEZING POINT Not applicable

EVAPORATION RATE: Less than 1 (Butyl Acetate = 1)



85 Jetson Lane, Central Islip, New York 11722 516.935.4000 Fax 516.935.4039

> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

VISCOSITY: Not applicable

PARTITION COEFFICIENT

N-OCTANOL / WATER: Not Determined

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY: None.

10.2 CHEMICAL STABILITY: Stable.

10.3 HAZARDOUS REACTIONS: None.

HAZARDOUS POLYMERIZATION: None.

10.4 CONDITIONS TO AVOID: None.

10.5 INCOMPATIBLE MATERIALS: Strong acid, alkali, oxidizing agents, bases.

10.6 HAZARDOUS DECOMPOSITION

OF PRODUCTS:

Oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

NOTE: Primary route of entry is through skin, with secondary route through inhalation.

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS: FOR INGREDIENTS

STODDARD SOLVENT (CAS #) 8052-41-3			
LD50 Oral Rat > 5,000 mg/kg			
LD50 Dermal Rabbit	> 3,000 mg/kg		
LC50 Inhalation Rat	> 13.1 mg/L, 4 hr.		

CRISTOBALITE (SiO2) QUARTZ (CAS #) 14464-46-1			
LD50 Oral Rat > 22,500 mg/kg			
LD50 Dermal Rabbit	NO DATA		
LC50 Inhalation Rat	NO DATA		

KAOLIN (CAS #) 1332-58-7			
LD50 Oral Rat	> 5,000 mg/kg		
LD50 Dermal Rabbit	> 5,000 mg/kg		
LC50 Inhalation Rat	> 46 mg/L, I HR.		

ACUTE TOXICITY: FOR PRODUCT

LD50: Not determined.

SKIN: Not determined.

INHALATION: Not determined.

INGESTION: Not determined.



11.2 POTENTIAL ACUTE HEALTH EFFECTS:

85 JETSON LANE, CENTRAL ISLIP, NEW YORK 11722 516.935.4000 Fax 516.935.4039

> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

SKIN:	Irritation and drying during prolonged contact.

EYES: Will cause eye abrasion, irritation, and possible cornea damage upon direct contact.

RESPIRATORY: Will irritate nose and throat when breathing high concentrations.

INGESTION: Will cause serious gastric disturbances.

SYMPTOMS AFTER CONTACT:

SKIN: Irritation, dryness, redness.

EYES: Pain, watering, burning.

RESPIRATORY: Irritation, asthmatic systems, dizziness.

INGESTION: Stomach pain, gastric disturbances.

11.2CHRONIC HEALTH EFFECTS:

Short and Long Term Exposure - Repeated Dose Toxicity:

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling and sometimes fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Acute silicosis causes decreased lung function and can result in heart disease secondary to the lung disease or heart failure. Death from acute silicosis can occur within months to a few years of disease onset. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop mycobacterial infections (tuberculosis and non-tuberculosis) and fungal infections. Inhalation of air with a very high concentration of respirable silica dust can cause the most serious forms of silicosis in a matter of months, or a few years. Accelerated silicosis results from exposure to high levels of airborne respirable carcinogenic crystalline silica and usually occurs within 2 – 10 years of initial exposure. Some epidemiologic studies have concluded that there is significant risk of developing silicosis even at airborne exposure levels that are equal to the recommended NIOSH REL, and ACGIH TLV.

11.3 CARCINOGENICITY:

<u>Carcinogenicity</u>: The International Agency for Research on Cancer (IARC) has determined that crystalline silica is carcinogenic to humans (Group 1-carcinogenic to humans). Refer to IARC Monograph 100C, A Review of Human Carcinogens: Arsenic, Metals, Fibres, and Dusts (published in 2012) in conjunction with the use of these materials. The National Toxicology Program classifies respirable crystalline silica as "known to be a human carcinogen". Refer to the NTP 12th Report on Carcinogens (2011). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica quartz, as a suspected human carcinogen (A2).

NTP: Crystalline silica component is present at levels greater than or equal to 0.1% is identified as a

known to be a human carcinogen by NTP.

IARC: Crystalline silica component is present at levels greater than or equal to 0.1% is identified as a

Group 1 carcinogen by IARC.

OSHA: NTP classification as known carcinogen meets definition of OSHA Table C-1 classification criteria.



> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

SECTION 12: ECOLOGICAL INFORMATION

12.1 TOXICITY: **INFORMATION FOR INGREDIENTS:**

STODDARD SOLVENT (CAS #) 8052-41-3				
LC50 Fish, Pimephales promelas	0.72 mg/L, 96 hr			
EC50 Daphnia magna	0.36 mg/L, 48 hr			

CRISTOBALITE (SiO2) QUARTZ	(CAS #) 14464-46-1
LC50 Fish, Pimephales promelas	NO DATA
EC50 Daphnia magna	NO DATA

KAOLIN (CAS #) 1332-58-7)				
LC50 Oncorhynchus mykiss 100 mg/l, 96 hr.				
LC50 Daphnia magna	1,100 mg/l, 48 hr.			
LC50 Scenedesmus subspicatus	1,100 mg/l, 72 hr.			

12.2 PERSISTENCE AND DEGRADABILITY: Not determined.

12.3 BIOACCUMULATIVE POTENTIAL: Not determined.

12.4 MOBILITY IN SOIL: Not determined.

12.5 RESULTS OF PBT and vPvB

ASSESSMENT

Not determined.

12.6 OTHER ADVERSE EFFECTS: No known or other significant effects or critical hazards.

SECTION 13: DISPOSAL INFORMATION

13.1 WASTE TREATMENT METHODS:

For small spills, contain all residues with inert absorbent material and dispose in chemical recycle container. For large spills, stop leak if safe to do so. Approach release from upwind. Dyke or dam area and vacuum all wet areas for recycle by a licensed waste disposal contractor. Avoid contact with soil, waterways, drains, and sewers unless such drains and sewers are fully compliant with the requirements of all authorities for disposal. Consult all federal, state, and local regulatory authorities for proper disposal.



> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

SECTION 14: TRANSPORTATION INFORMATION

REGULATORY INFORMATION	UN NUMBER	PROPER SHIPPING NAME	CLASSES	PACKING GROUP	LABEL	ADDITIONAL INFORMATION
DOT	NOT	NOT	NOT	NOT	NONE	NONE
CLASSIFICATION	APPLICABLE	APPLICABLE	APPLICABLE	APPLICABLE	NONE	NONE
TDG	NOT	NOT	NOT	NOT	NONE	NONE
CLASSIFICATION	APPLICABLE	APPLICABLE	APPLICABLE	APPLICABLE	NONE	HONE
ADR/RID	NOT	NOT	NOT	NOT	NONE	NONE
CLASSIFICATION	APPLICABLE	APPLICABLE	APPLICABLE	APPLICABLE	NONL	NONE
IMDG	NOT	NOT	NOT	NOT	NONE	NONE
CLASSIFICATION	APPLICABLE	APPLICABLE	APPLICABLE	APPLICABLE	NONE	NONE
IATA/IACO	NOT	NOT	NOT	NOT	NONE	NONE
CLASSIFICATION	APPLICABLE	APPLICABLE	APPLICABLE	APPLICABLE	NONE	NONE

SECTION 15: REGULATORY INFORMATION

15.1U.S. FEDERAL REGULATIONS:

OSHA HAZARD COMMUNICATION

STANDARD:

Non-regulated.

TSCA: All ingredients are listed on the TSCA inventory.

SARA (302/304): Non-regulated, no reportable or EHS quantities.

SARA (311/312): Acute health hazard. Chronic health hazard.

SARA TITLE III (313): This product contains the following chemicals subject to the reporting requirements of

Section 313: None

OTHER REGULATORY STANDARDS: Non-regulated per 29 CFR 1900.1000 - 1500, 40 CFR PART 261.3, 302.4, 355, 370, 372.

15.2 STATE REGULATIONS: CALIFORNIA PROPOSITION 65: This product contains the following chemicals known by the

state of California to cause cancer, birth defects, or any other reproductive harm:

CRISTOBALITE (SiO₂) QUARTZ (14464-46-1).

15.3 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS / LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE:

U.S. OSHA 29CFR 1910.1000 - 1500

REGULATION (EC) 1907/2006 - REACH (ANNEX X1V)

EC REGULATIONS 1272/2008 - CLP

EH40 / 2005 - WORKPLACE EXPOSURE LIMITS (WHERE APPLICABLE)

CONTROL OF SUBSTANCE HAZARDOUS TO HEALTH - COSHH

DANGEROUS SUBSTANCES AND EXPLOSIVE ATMOSPHERE REGULATIONS - DSEAR



> WWW.NUVITECHEMICAL.COM WWW.UNIVERSALPHOTONICS.COM

SAFETY DATA SHEET: NU-POL

REGULATION (EC) – REACH ANNEX (XIV) ARTICLE 59(10) AUTHORIZATIONS AND / OR RESTRICTIONS ON USE: Contains the following REACH (SVHC) Candidate Substances: NONE.

REGULATION (EC) 2015/863 - RoHS

Contains the following RoHS Substances: NONE

NATIONAL REGULATIONS: Non-regulated per EINECS / ELINCS / DSL / NDSL / IECSC / ENS / ECL / PICCS.

SECTION 16: OTHER INFORMATION

HMIS RATING: Health 2, Flammability 2, Reactivity 0, Personal Protection H

NFPA RATING: Health 2, Flammability 2, Reactivity 0



DEFINITIONS:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR/RID: International carriage of dangerous goods by road or rail

CLP: Classification, Labeling and packaging

DOT: Department of Transportation

EC: Commission Regulation (European Union)

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer

IATA/IACO: International Air Transport Association / International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods

LTEL: Long Term Exposure Limit
NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

REACH: Registration, Evaluation, Authorization and Restriction (European Union)

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

SVHC: Substances of Very High Concern (European Union)
TDG: Transportation of dangerous goods -- Canada

WEL: Workplace Exposure Limit

DISCLAIMER

Information included herein was obtained from sources which Universal Photonics, Inc. believes are reliable and accurate as of the date hereof. HOWEVER, NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREIN AS TO THE INFORMATION PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The health and safety precautions contained herein may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. Universal Photonics, Inc. ASSUMES NO LEGAL LIABILITY FOR ANY INJURY, ACCIDENT, LOSS, OR DAMAGE THROUGH THE USE OF THIS PRODUCT.